

DragonFire Racing

2330 W. Broadway Rd #112

Mesa, AZ 85202

1 (800) 708-9803

WWW.DRAGONFIRERACING.COM



FEEL THE HEAT!

RacePace Flying-V Installation Instructions

Congratulations on your purchase of the Race Pace Flying-V. As part of our Race Pace modular cage system the Flying-V is designed to give you more protection out front of the cab. Attaching at 3 different points, the Flying-V provides protection over the stock open front style cage as well as aggressive styling.



- *Do not use if there is any sign of damage to product
- *Frequently inspect all hardware to ensure everything is secure
- *Replacement may be required in the event of a roll over
- *This product may inhibit line of sight in some instances

Disclaimer

Off road activities can be hazardous and could lead to injury, dismemberment, paralysis and death. No warranty of representation is made as to the products ability to protect the user from any injury or death. The user assumes that risk. The acceptance and /or use of this merchandise purchased from DragonFire by the customer hereby shall release DragonFire from any and all liability pertaining to the use of such merchandise.

Tools Required
3/16 Allen Wrench
5/16 Allen Wrench

Step 1: Remove all pieces from packaging, make sure that all pieces are accounted for and not damaged. (If there is missing or damaged product please contact your authorized DragonFire dealer)

Step 2: Remove all six bolts and top portion of cage clamp from each cage clamp (**A, B, C**) using 3/16 Allen wrench.

Step 3: Remove both OE cage bolts and nuts from forward cage bung on passenger (**D**) side using 5/16 Allen wrench. This will allow for added clearance during install.



Step 4: Place Flying-V inside front portion of cage, check to see that all cage clamps are sitting flush against cage. Loosely re-install top piece and all six bolts to cage clamp **(B)**.

Step 5: Re-Install stock hardware to forward cage bung on passenger side **(D)**. ***Check owner's manual for torque specifications***

Step 6: Re-Install top pieces and bolts to all cage clamps **(A, B, C)** using 3/16 Allen wrench. Evenly tighten each bolt until snug **(7 Foot Pounds Torque)**. Installation is now complete.

PRO Tip:

Regularly check all bolts on Flying-V to ensure they are snug (7 Foot Pounds)

For further assistance please contact your authorized DragonFire dealer.